

HT2 BASE

Product information

Robust table microphone for control rooms

- High stability with the big foot plate
- Durable and long connecting cable
- Connection to nearly any VCS or control room system
- Perfect handling due to the ergonomic form
- Easy to use Push-To-Talk button
- Option with USB available



TECHNICAL BASICS

MICROPHONE

| | |
|--------------------|--------------------------|
| Working principle | Electret |
| Direction | Omni- directional |
| Impedance | 2,2k Ω (1kHz) |
| Frequency response | 50Hz to 16kHz |
| Sensitivity | 7,9mV/Pa/ 1kHz \pm 3dB |
| Power consumption | 1.5V to 10V (DC) |
| S/N ratio | > 58dB (1kHz) |

SWITCH

| | |
|----------|------|
| IP Class | IP40 |
|----------|------|

ADDITIONAL DATA

| | |
|----------------------|--------------|
| Weight | 400g |
| Temperature range | 0°C to +40°C |
| Dimensions (Height) | 207mm |
| Diameter base | 88mm |
| Dimensions PTT (LxW) | 18mm x 26mm |
| Colour housing | Black |
| Colour PTT-button | silver |

HOUSING

| | |
|-----------------------|---------|
| Material (housing) | POM |
| Material (PTT-button) | AlMgSi1 |

More information about the Product and the corresponding accessories, connection cable and scope of delivery can be found at www.imtradex.de.

TD-HT2-BSE-B-2021-EN