

# PTT BUTTON PTT-8 DYNAMIC

## Product information

Our robust PTT button for flexible usability

- Dynamic version support headset such as Peltor ComTac XPI or CH3/Ch5
- Dust protection and protection against splash water
- High durability with glass fiber reinforced synthetic material
- Clothing clip 180° turnable
- Push button available in yellow with phosphorescent material
- Silent version for PTT button available



## TECHNICAL DATA

### GENERAL INFORMATION

Dimensions (l x w x h)	76 mm x 50 mm x 33 mm
Colour	Black
Weight	70 g
Operation temperature	- 30 °C to + 75 °C
IP protection class	IP 54

### HOUSING

Material definition	Durethan BKV FN00 0000
Material description	PA6, 30 % GF, halogen-free, flame-retardant
Flammability	UL94 - V0
RoHs	YES
REACH	YES

### PTT SWITCH

Dimensions (D)	40 mm
Colour	Black/ yellow afterglowing
Contact resistance	≤ 100 mΩ
Insulation resistance	≥ 10 MΩ
Lifetime	≥ 1,500,000 cycles
Tactile path	1.8 mm
Actuation force	2.5 N

### CABLES AND CONNECTORS

Connector (headset)	Nexus
Connector (radio)	acc. to customer request